

Leaf Porometer model SC-1

- Automatic Sampling Mode Removes User Subjectivity
- No Daily Calibration
- No Tubes, Pumps, Fans, Moving Parts Or Heavy Equipment
- Accurate Steady-state
 Measurement
- Very Simple, Easy-touse Interface
- Includes Software Utility For Downloading Data
- Low Cost "AA"
 Alkaline-battery
 Powered
- Non-destructive

Applications

- Water use and water balance.
- Water stress measurements.
- Herbicide and pollutant uptake studies.
- Research on stomatal functions.
- Teaching and student labs.



► The Leaf Porometer has an easy-to-use menudriven interface, allowing you to use and manage your data. You can also add notes and comments to your saved data for later data analysis. The Leaf Porometer includes a user-friendly software utility for downloading data to your computer.

SPECIFICATIONS

Conductance range

0 to 500 mmol m⁻² s⁻¹

Operating Environment

5 to 40 °C, 10 to 90% RH, non-condensing

Power

4 AA alkaline cells

Battery life

More than 1 year

Data storage

4095 measurements in flash memory

Interface

9 pin serial RS232 interface

Measurement aperture

6.3 mm (0.25") diameter

Sensor head cable length

1.2m (4ft)


Manual and Auto Read mode options

Measurement time in Auto mode

30 seconds

Units

mmol m⁻²s⁻¹, m²s mol⁻¹, s/m



Leaf Porometer

Porous Teflon Filter Disk



950 NE Nelson Court Pullman, Washington 99163 800-755-2751 International 509-332-2756 fax 509-332-5158 www.decagon.com/porometer leafporometer@decagon.com